















- Dynamic Brain Functional Networks for Early MCI Detection,” *IEEE Trans. Med. Imaging*, Vol. 32, No. 2, pp. 478–487, 2020.
- [26] M. Tofighi, T. Guo, J.K.P. Vanamala, and V. Monga, “Prior Information Guided Regularized Deep Learning for Cell Nucleus Detection,” *IEEE Trans. Med. Imaging*, Vol. 38, No. 9, pp. 2047–2058, 2019.
- [27] J. Djhonson (2020) “Brain MRI Images for Brain Tumor Detection,” [Online], <https://www.kaggle.com/jjprotube/brain-mri-images-for-brain-tumor-detection>, access date: 13-Dec-2020.
- [28] S. Aggarwal and N. Chugh, “Signal Processing Techniques for Motor Imagery Brain Computer Interface: A Review,” *Array*, Vol. 1–2, pp. 1–12, 2019.
- [29] K. He, X. Zhang, S. Ren, and J. Sun, “Deep Residual Learning for Image Recognition,” *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.
- [30] V. Nair and G.E. Hinton, “Rectified Linear Units Improve Restricted Boltzmann Machines,” *27th International Conference on Machine Learning (ICML-10)*, 2010, pp. 807–814.
- [31] O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, A.C. Berg, and L. Fei-Fei, “ImageNet Large Scale Visual Recognition Challenge,” *Int. J. Comput. Vis.*, Vol. 115, pp. 211–252, 2015.
- [32] T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, and C.L. Zitnick, “Microsoft COCO: Common Objects in Context,” *European Conference on Computer Vision*, 2014, pp. 740–755.
- [33] F. Chollet, “Xception: Deep Learning with Depthwise Separable Convolutions,” *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 1800–1807.
- [34] J. Deng, W. Dong, R. Socher, L. Li, K. Li, and L. Fei-fei, “ImageNet: A Large-Scale Hierarchical Image Database,” *2009 IEEE Conference on Computer Vision and Pattern Recognition*, 2009, pp. 248–255.
- [35] C. Szegedy, S. Ioffe, V. Vanhoucke, and A. Alemi, “Inception-v4, Inception-ResNet and the Impact of Residual Connections on Learning,” *Thirty-First AAAI Conference on Artificial Intelligence (AAAI’17)*, 2017, pp. 4278–4284.
- [36] B. Zoph, G. Brain, and J. Shlens, “Learning Transferable Architectures for Scalable Image Recognition,” *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2018, pp. 8697–8710.
- [37] K. Simonyan and A. Zisserman, “Very Deep Convolutional Networks for Large-Scale Image Recognition,” *International Conference on Learning Representations*, 2015, pp. 1–14.
- [38] K. Radhika, K. Devika, T. Aswathi, P. Sreevidya, V. Sowmya, and K.P. Soman, “Performance Analysis of NASNet on Unconstrained Ear Recognition,” in *Nature Inspired Computing for Data Science*, M. Rout, J. K. Rout, and H. Das, Eds., New York, USA: Springer International Publishing, 2020, pp. 57–82.
- [39] G. Huang, Z. Liu, L. Van Der Maaten, and K.Q. Weinberger, “Densely Connected Convolutional Networks,” *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 2261–2269.
- [40] T. Kohonen, “Self-organized Formation of Topologically Correct Feature Maps,” *Adv. Comput. Neurosci. Control Inf. Theory Biol. Syst.*, Vol. 43, No. 1, pp. 59–69, 1982.
- [41] J. Yosinski, J. Clune, Y. Bengio, and H. Lipson, “How Transferable are Features in Deep Neural Networks?” *Proc. 27th International Conference on Neural Information Processing Systems*, 2014, Vol. 2, pp. 3320–3328.
- [42] A. Sharif, R. Hossein, A. Josephine, and S. Stefan, “CNN Features Off-the-Shelf: An Astounding Baseline for Recognition,” *IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2014, pp. 512–519.
- [43] B. Zhou, A. Lapedriza, J. Xiao, A. Torralba, and A. Oliva, “Learning Deep Features for Scene Recognition using Places Database,” *Advances in Neural Information Processing Systems 27 (NIPS 2014)*, 2014, pp. 487–495.